# D467ML

- 46" Metal Frame (Full HD)
- Resolution 1920 x 1080
- Brightness 700cd/㎡
- Contrast Ratio 4000:1

| | | | |
|---|---|---|---|
| **Display Panel** | Screen size | | 46 inch Wide |
| | Active Display Area (mm) | | 1018.08 x 572.67 mm |
| | Number of Pixels | | 1920 x 1080 (WUXGA) |
| | Viewing Angle (H/V) | | 178º/178º (CR≥10) |
| | Brightness | | 700cd/㎡ |
| | Contrast Ratio | | 4000:1 |
| | Bezel Size (U/D/L/R)(mm) | | 11.5/11.5/11/11 |
| | Out Line Dimension (mm) | | 1047.4 x 600.6 x 66.0 mm |
| | Display Color | | 16.7 Million |
| | Life Time | | 50,000h average |
| **Resolution (Max)** | Monitor | | 1920 x 1080 |
| | DTV | | 1080p |
| **Connectivity & Control** | Input | | VGA(15pin D-sub), HDMI, RS232C<br>Composite(BNC), Component (BNC)<br>PC/Composite/Component Audio |
| | Output | | VGA(15pin D-sub), HDMI, Composite(BNC),<br>Component(BNC), RS232C, Speaker(Ready) |
| | Auto Cooling System | | Yes (1EA) |
| | Auto Power Control (DPMS) | | Yes |
| **Feature** | Tempered Glass | | Option (D467MLG) |
| | Touch Screen (IR multi-touch) | | Option (D467MLI) |
| **Power Requirement** | Input Voltage | | 100 – 240 VAC |
| | Consumption (Watt) | | 260W |
| | DPMS (Watt) | | 1W |
| **Mechanical** | Dimension | Unit | 1051.2 x 604.4 x 128.3 mm |
| | Weight | Unit / Packed | 32kg / 37kg |
| **Approvals** | EMI/EMC | | FCC, CE |
| | Safety | | cTUVus, TUV, CB |
| **Accessory** | Power Cord, HDMI Cable (Option : DVI to HDMI / D-SUB / RS-232C / Audio Cable) | | |
| **Temperature** | 0℃ - 40℃ | | |
| **Humidity** | 20% - 80% | | |
| **Wall Mounting Hole** | 600 x 200, 600 x 400 mm | | |

HYUNDAI
HYUNDAI IT CORP.